



Primo Tile Grout (Polymer Based)

Description

A high quality polymer-modified, water resistant, cement based grout designed for grouting glazed wall tiles, porcelain tiles, mosaic, vitrified & fully vitrified tiles, natural and engineered stones.

Benefits

- Good bond strength
- Water resistant
- For interior & exterior use
- Available in range of colours
- Suitable for joint width of 1 - 6 mm

Coverage Estimates

Pack Size
1kg. | 1kg. x 10 | 1kg x 30
Consumption depend on joint width, size of tiles.



Primo Polymer Based Super Grout

Description

Primo is a high quality, high polymer - modified, high performance grout with excellent water - repellent and efflorescence resistance properties designed for grouting glazed tiles, mosaic, vitrified and fully vitrified tiles, ceramic tiles, industrial tiles, granites, marbles & other natural stones etc. Primo Grout Combo has higher strength, water and stain resistance compared to normal cement grout.

Benefits

- Excellent water repellent property
- Non-shrink
- Better efflorescence and stain resistance
- Suitable for joint width of 1 - 6 mm
- For interior & exterior use
- Available in range of colours

Coverage Estimates

Pack Size - 1kg. | 1kg. x 20
Consumption depend on joint width, size of tiles.

BASIC COLORS (FOR EPOXY/GROUTS ONLY)

019	PISTA
020	PAPAYA
021	TERRACOTTA
022	GOLDEN
023	LIME COLOR

METALLIC COLORS

M 051	METALLIC COPPER
M 052	METALLIC GREY
M 053	METALLIC PALE GOLD
M 054	METALLIC BLACK

STAR COLORS

S 071	GOLDEN SPARKLE GOLD
S 072	DARK BROWN SPARKLE GOLD
S 073	BLACK SPARKLE GOLD
S 074	DARK GREY SPARKLE SILVER

NIGHT GLOW

NG 091	NIGHT GLOW GREEN
NG 092	NIGHT GLOW BLUE

Shades shown are for indication only.

Primo Heavy Duty Tile Cleaner



Features

- Powerful formula.
- Fast acting.
- Easy to apply.
- Removes cement film.
- Removes residues most oxide stains Pack.

Pack Size - 500 ml | 1ltr. | 5 ltr.



Primo Grout Admix

Features

- Improves the flexibility for Cement Polymer Grouts, Super Grouts & Wide Joint Grouts
- Improves the strength
- Improves the water resistance
- Increase the abrasion resistance of Grouts

Pack Size - 100 ml | 400 ml



Primo Marble Cleaner


Pack Size 500 ml



Primo Tile Spacer


Available in (mm) 2,3,4,5,6,8&10

PRIMO Notched Trowel



Available in 6x6mm & 9x9mm notched trowel suitable for 3mm & 4.5mm bed thickness respectively.

PRIMO Tile Leveling System



Available in (mm) 2,3,4,5,8&10



PRIMO CHEMICALS INDIA
E-mail : primochemicals07@gmail.com



By - 99153 55000



Primo™

COMMITTED TO SUPERIOR QUALITY & RESULTS



www.facebook.com/primochemical

www.instagram.com/primochemical

BASIC COLORS (FOR EPOXY/GROUTS ONLY)

001	WHITE
002	IVORY
003	BEIGE
004	DARK BROWN
005	BLACK
006	LIGHT GREY
007	DARK GREY
008	ROYAL BLUE
009	ELECTRIC BLUE
010	ALPINE BLUE
011	AQUA GREEN
012	PALE GREEN
013	BOTTLE GREEN
014	OLIVE GREEN
015	YELLOW GREEN
016	BLOOD RED
017	RED BROWN
018	WOODEN

Note : Exact matching of the colours / shades cannot be guaranteed.

SIVER STAR Tile Adhesive 220 P



Description

Polymer modified grey cement-based adhesive, suitable for fixing ceramic tiles for floors & walls in interior situations. Suitable for fixing ceramic tiles upto 6 mm bed thickness (can be extended up to 12 mm thickness in area of limited extent).

Benefits

- Good Bond Strength.
- Water Resistant.
- Easy Mixing & Application.

Coverage Estimates

Pack Size - 20 kg.
Approx. 3 kg/m² using a 6mm x 6mm square notch trowel.

SIVER STAR Tile Adhesive 660 Super Plus



Description

Grey cement based, water & frost resistant, high polymer modified, high strength adhesive for fixing tile and stone on wall/floor in interior/exterior situations upto 6mm bed thickness (can be extended up to 12 mm in area of limited extent). The set adhesive is water resistant and suitable for use in swimming pools. 660 Super Plus is used for fixing ceramic, vitrified & fully vitrified tiles, glass mosaic, porcelain, terrazzo, metal or glass tiles, non staining natural stone and engineered stone.

Benefits

- Very high performance and strength.
- Premium multi use adhesive
- Excellent water and frost resistance

Coverage Estimates

Pack Size - 20 kg.
Approx. 2.5 kg/m² using a 6mm x 6mm square notch trowel.

WHITE STAR Tile Adhesive 777 Plus



Description

High polymer modified, white cement based tile adhesive suitable for fixing wall and floor tile/stone in interior and exterior situations up to 6mm bed thickness (can be extended up to 12 mm in area of limited extent). The set adhesive is water-resistant and is suitable for use in showers and wet areas. By addition of PRIMO LATEX ADMIX is suitable for use in totally submerged conditions such as swimming pools.

Benefits

- Very high performance and strength.
- Premium multi use adhesive
- Excellent water and frost resistance

Coverage Estimates

Pack Size - 20 kg.
Approx. 2.5 kg/m² using a 6mm x 6mm square notch trowel.

STONE Adhesive 1109



Description

Stone Adhesive is a high polymer modified & highly flexible adhesive with enhanced properties of slip resistant, extended open time & excellent bond strength which is necessary for fixing large format tiles/ natural stones & slim tiles on vertical & horizontal surface for indoor as well as outdoor application especially in external conditions & on substrates subject to deformations/vibrations.

Benefits

- Highly Polymer modified – excellent bond strength at different conditions.
- Extended open time - suitable for large format & external condition.

- Sag Resistant formula - for hassle-free application on vertical walls.
- Water & shock resistant - suitable for wet areas & commercial floor too.
- Sustains heat ageing – Idea for external & high temperature applications.
- Highly deformable adhesive - sustains substrate vibration.
- LowVOC - for healthy living

SIVER STAR TILE Adhesive 440 Plus



Description

High polymer modified, grey cement based tile adhesive suitable for fixing wall and floor tile/stone in interior and exterior situations up to 6mm bed thickness (can be extended up to 12 mm in area of limited extent). The set adhesive is water-resistant and is suitable for use in showers and wet areas. By addition of PRIMO LATEX ADMIX is suitable for use in totally submerged conditions such as swimming pools.

Benefits

- High bond strength.
- Easy mixing, Smooth Application & better workability
- Water Resistant

Coverage Estimates

Pack Size - 20 kg.
Approx. 3 kg/m² using a 6mm x 6mm square notch trowel.

WHITE STAR Tile Adhesive 555 P



Description

Polymer modified white cement-based adhesive, suitable for fixing ceramic tiles for floors & walls in interior situations. Suitable for fixing ceramic tiles up to 6 mm bed thickness (can be extended up to 12 mm thickness in area of limited extent).

Benefits

- Good Bond Strength.
- Water Resistant.
- Easy Mixing & Application.

Coverage Estimates

Pack Size - 20 kg.
Approx. 3 kg/m² using a 6mm x 6mm square notch trowel.

WHITE STAR Tile Adhesive 999 Super Plus



Description

White cement based, water & frost resistant, high polymer modified, high strength adhesive for fixing tile and stone on wall/floor in interior/exterior situations upto 6mm bed thickness (can be extended up to 12 mm in area of limited extent). The set adhesive is water resistant and suitable for use in swimming pools. 999 Super Plus is used for fixing ceramic, vitrified & fully vitrified tiles, glass mosaic, porcelain, terrazzo, metal or glass tiles, non staining natural stone and engineered stone.

Benefits

- Very high performance and strength.
- Premium multi use adhesive
- Excellent water and frost resistance

Coverage Estimates

Pack Size - 20 kg.
Approx. 2.5 kg/m² using a 6mm x 6mm square notch trowel.

Primo Epoxy Adhesive



Description

For attaching small- and large-format tile and stone to walls and floors, PRIMO EPOXY Adhesive is a three-part, highly durable, chemical-resistant adhesive. For fastening tile and stone to metal, glass, aluminum, plywood etc. surfaces, it offers exceptional, long-lasting binding strength. PRIMO epoxy adhesive is suitable for both inside and exterior damp locations. Due to its chemical resistance, it can also be used in commercial installations that are located in chemically vulnerable regions, such as food processing facilities, commercial kitchens, dining establishments, high-traffic areas, and workshop spaces.

Benefits

- Excellent adhesion properties, tiles & stone can be fixed on surface like metal sheet, aluminum panels, glass, plywood etc | Fixing Tiles & Stones on Ceilings & Elevated Structures | Provides high strength and durable resistance | Can be used on floor & Wall in Chemical Prone Areas | Provides strength at higher height level Where cement based adhesive has limitations.

Coverage Estimates

Pack Size - 5 kg., 10 kg. The consumption will vary depending on surface undulations.

FLEX Adhesive



Description

Two-part, white adhesive comprising of rubber-based powder and water based polymer liquid. Flexible adhesive for use in areas where tiling is likely to be subjected to some limited background movement or vibration, especially wood, plywood & metal surface.

Benefits

- High bond strength.
- Easy mixing, Smooth Application.
- Water Resistant

Coverage Estimates

Pack Size - 20 kg.
Approx. 3 kg/m² using a 6mm x 6mm square notch trowel.

Primo Epoxy Grout



Description

EPOXY GROUT is hygienic, hard-wearing, impervious, 2 component epoxide resin-based grout with a high degree of resistance to chemical attack, abrasion and impact. The cured grout does not transfer taints to food products, prevents the entry of bacteria or dirt and is easily maintained in a sterile condition. EPOXY GROUT is designed for grouting glazed tiles, mosaic, vitrified and fully vitrified tiles, ceramic tiles, industrial tiles, granites, marbles & other natural stones etc.

Benefits

- Hygienic and chemical resistant | Stain and bacterial resistant | Provides high strength and durable joints | Suitable for submerged conditions | Water based : easy to be cleaned from tiled surface | Suitable for joint width of 1 - 12 mm | For interior & exterior use Available in range of colours.

Coverage Estimates

Pack Size - 1 kg, 1.5 kg. Consumption depend on joint width, size of tiles.